

View Online at <https://aerobasegroup.com/nsn/5306-01-350-0651>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.397 inches

**Fastener Length:**

Between 2.318 inches and 2.365 inches

**Head Style:**

Double hexagon

**Head Height:**

Between 0.154 inches and 0.174 inches

**Width Between Flats:**

0.439 inches

**Grip Diameter:**

Between 0.2490 inches and 0.2495 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.081 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 1.927 inches and 1.947 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.197 inches first hole and 2.254 inches first hole

**Material:**

Steel comp xm-13

**Material Specification:**

St3-453, cage76301 mfr ref single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0