## NSN 5306-01-350-2241

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-350-2241 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.412 inches **Fastener Length:** Between 1.397 inches and 1.427 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.290 inches and 0.310 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.428 inches and 0.438 inches **Extended Washer Thickness:** Between 0.059 inches and 0.079 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.990 inches and 1.010 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5306-01-350-2241

Shear Bolt - Page 2 of 2



| ш | ın | 10 | <i>(</i> )+ | Measure: |  |
|---|----|----|-------------|----------|--|
|   |    |    |             |          |  |

--

Demilitarization:

No

Fiig:

A003b0