## NSN 5306-01-350-2902

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-350-2902

view Online at https://derobasegroup.com/hsh/0000-01-000-2002
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.440 inches
Fastener Length:
Between 3.674 inches and 3.721 inches
Head Style:
Double hexagon
Head Height:
Between 0.680 inches and 0.700 inches
Width Between Flats:
Between 1.801 inches and 1.814 inches
Grip Diameter:
Between 1.2485 inches and 1.2490 inches
Shank Unthreaded Hole Diameter:
0.136 inches first hole and 0.146 inches first hole
Thread Diameter:
1.250 inches
Grip Length:
2.250 inches
Thready Qty Per Inch (tpi):
12
Min. Tensile Strength (psi):
220000 pounds per square inch
Distance From Head Largest Bearing Surface To Shank Hole Center:
3.395 inches first hole
Surface Finish:
32.0 microinches grip
Product Name:
Navy special project
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response

Unjf

## NSN 5306-01-350-2902

Shear Bolt - Page 2 of 2



_					
CI	~~	14	I i	ife:	
J.	16			HE.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0