NSN 5306-01-350-3153



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-350-3153 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.705 inches **Fastener Length:** Between 1.815 inches and 1.845 inches **Head Style:** Spline extended washer **Head Height:** Between 0.383 inches and 0.403 inches **Extended Washer Diameter:** Between 0.807 inches and 0.817 inches **Extended Washer Thickness:** Between 0.053 inches and 0.073 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Head Minor Diameter:** 0.514 inches **Thread Diameter:** 0.437 inches **Grip Length:** Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unjf

Shelf Life:

N/a

NSN 5306-01-350-3153

Shear Bolt - Page 2 of 2



	• •						
ın	1+	Of	ΝЛ	ດລ	CI.	ırı	ο.

--

Demilitarization:

No

Fiig:

A003b0