NSN 5306-01-350-5314

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-350-5314 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.152 inches **Fastener Length:** Between 3.637 inches and 3.667 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.673 inches Width Between Flats: 0.917 inches **Extended Washer Diameter:** Between 1.185 inches and 1.195 inches **Extended Washer Thickness:** 0.125 inches **Hole Diameter:** Between 0.065 inches and 0.075 inches **Grip Diameter:** Between 0.6230 inches and 0.6240 inches **Thread Diameter:** 0.625 inches **Grip Length:** Between 2.490 inches and 2.510 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 260000 pounds per square inch **Hole Configuration Style:** Double hexagon longitudinal hole Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads **Product Name:** Navy special project Material:

Cobalt comp mp-35-n

NSN 5306-01-350-5314

Close Tolerance Bolt - Page 2 of 2

No Fiig: A003b0



Material Specification:
Ams 5844 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: