## NSN 5306-01-350-8233

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-350-8233 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.725 inches **Fastener Length:** Between 2.335 inches and 2.365 inches **Head Style:** Spline drive shear head **Head Height:** Between 0.318 inches and 0.338 inches **Grip Diameter:** Between 0.5610 inches and 0.5615 inches **Shank Unthreaded Hole Diameter:** 0.141 inches first hole and 0.146 inches first hole **Head Minor Diameter:** 0.901 inches **Thread Diameter:** 0.562 inches **Grip Length:** Between 1.615 inches and 1.635 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 125000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 2.216 inches first hole and 2.236 inches first hole Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5306-01-350-8233

Close Tolerance Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0