NSN 5306-01-351-1469

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-351-1469 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** Between 0.923 inches and 0.953 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.225 inches and 0.245 inches Width Between Flats: Between 0.347 inches and 0.361 inches **Extended Washer Diameter:** Between 0.465 inches and 0.475 inches **Extended Washer Thickness:** Between 0.032 inches and 0.052 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-335 federal specification single treatment response **Thread Series Designator:**

Unjf

Shelf Life:

N/a

NSN 5306-01-351-1469

Shear Bolt - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A003b0