NSN 5306-01-351-3238

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-351-3238 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.761 inches **Fastener Length:** Between 1.933 inches and 1.963 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.494 inches and 0.514 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Extended Washer Diameter:** Between 0.818 inches and 0.828 inches **Extended Washer Thickness:** Between 0.113 inches and 0.133 inches **Grip Diameter:** Between 0.4990 inches and 0.4995 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 1.177 inches and 1.197 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Unji

Shelf Life:

N/a

NSN 5306-01-351-3238

Shear Bolt - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0