

View Online at <https://aerobasegroup.com/nsn/5306-01-351-3453>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.650 inches

**Fastener Length:**

1.625 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.150 inches and 0.162 inches

**Width Between Flats:**

Between 0.428 inches and 0.438 inches

**Hole Diameter:**

Between 0.062 inches and 0.066 inches

**First Diameter From Head:**

Between 0.181 inches and 0.188 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.975 inches

**Thread Diameter:**

0.250 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Features Provided:**

Dry film lubricant

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

130000 pounds per square inch

**Hardness Rating:**

24.0 rockwell c

**Minimum Yield Strength:**

85000 pounds per square inch

**Hole Configuration Style:**

Hexagon flats

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Nickel alloy k-500

**Material Specification:**

Qq-n-286 cla federal specification single material response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0