

View Online at <https://aerobasegroup.com/nsn/5306-01-351-3498>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.538 inches

**Fastener Length:**

Between 1.023 inches and 1.053 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.302 inches and 0.322 inches

**Extended Washer Diameter:**

Between 0.521 inches and 0.531 inches

**Extended Washer Thickness:**

Between 0.051 inches and 0.071 inches

**Grip Diameter:**

Between 0.3115 inches and 0.3120 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.081 inches first hole

**Head Minor Diameter:**

Between 0.360 inches and 0.375 inches

**Thread Diameter:**

0.3125 inches

**Grip Length:**

Between 0.490 inches and 0.510 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.835 inches first hole

**Surface Finish:**

32.0 microinches bearing surface of head 32.0 microinches grip 32.0 microinches threads

**Material:**

Nickel alloy 718

**Material Specification:**

Ams5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0