

View Online at <https://aerobasegroup.com/nsn/5306-01-351-3506>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.528 inches

Fastener Length:

Between 3.138 inches and 3.168 inches

Head Style:

Dished hexagon

Head Height:

Between 0.219 inches and 0.234 inches

Width Between Flats:

Between 0.678 inches and 0.690 inches

Locking Feature:

Patch threads or pellet threads or strip threads

Grip Diameter:

Between 0.4365 inches and 0.4370 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.437 inches

Grip Length:

Between 2.615 inches and 2.635 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.954 inches first hole

Surface Finish:

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

Material:

Plastic polyamide locking featureiron alloy 660 fastener

Material Specification:

Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener

Surface Treatment:

Passivate fastener

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Specification Data:

80205-nas6307 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0