

View Online at <https://aerobasegroup.com/nsn/5306-01-351-3508>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.895 inches

Fastener Length:

Between 3.388 inches and 3.418 inches

Head Style:

Dished hexagon

Head Height:

Between 0.500 inches and 0.515 inches

Width Between Flats:

Between 1.427 inches and 1.440 inches

Grip Diameter:

Between 0.9985 inches and 0.9990 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Thread Diameter:

1.000 inches

Grip Length:

Between 3.388 inches and 3.418 inches

Thready Qty Per Inch (tpi):

12

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.715 inches first hole

Surface Finish:

32.0 microinches bearing surface of head 32.0 microinches grip 32.0 microinches threads

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6316 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0