NSN 5306-01-351-3513

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-351-3513

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.323 inches
Fastener Length:
Between 0.746 inches and 0.776 inches
Head Style:
Dished hexagon
Head Height:
Between 0.110 inches and 0.125 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Locking Feature:
Patch threads or pellet threads or strip threads
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 0.428 inches and 0.448 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Color:
Green threads
Material:
Plastic polyamide locking featureiron alloy 660 fastener
Material Specification:
Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Surface Treatment:
Cadmium fastener and chromate fastener
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response fastener
Thread Series Designator:
Unjf
Specification Data:

80205-nas6303 professional/industrial association standard

NSN 5306-01-351-3513

Shear Bolt - Page 2 of 2



	L -	11		ife	_
3	ne	п	_	пе	Ξ

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0