## NSN 5306-01-351-5512

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-351-5512 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.425 inches **Fastener Length:** Between 3.910 inches and 3.940 inches **Head Style:** Dished hexagon **Head Height:** Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Shoulder Diameter:** 0.3115 inches first shoulder and 0.3120 inches first shoulder **Shoulder Length:** 3.490 inches first shoulder and 3.510 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): Distance From Head Largest Bearing Surface To Shank Hole Center: 3.722 inches first hole and 3.772 inches first hole **Shoulder Shape:** Round first shoulder Material: Iron alloy 660 **Material Specification:** Ams5732 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5306-01-351-5512

Shoulder Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0