NSN 5306-01-351-5515

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-351-5515 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.705 inches **Fastener Length:** Between 1.315 inches and 1.345 inches **Head Style:** Spline extended washer **Head Height:** Between 0.383 inches and 0.403 inches **Extended Washer Diameter:** Between 0.740 inches and 0.750 inches **Extended Washer Thickness:** Between 0.072 inches and 0.092 inches **Hole Diameter:** Between 0.050 inches and 0.060 inches **Grip Diameter:** Between 0.4365 inches and 0.4370 inches **Head Minor Diameter:** 0.514 inches **Thread Diameter:** 0.438 inches **Grip Length:** Between 0.615 inches and 0.635 inches **Hole Quantity:** Hole Type:

Drilled

Thready Qty Per Inch (tpi):

Min. Tensile Strength (psi):

180000 pounds per square inch

Hole Configuration Style:

Spline

Surface Finish:

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

NSN 5306-01-351-5515

Shear Bolt - Page 2 of 2

A003b0



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia: