NSN 5306-01-351-7070



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-351-7070 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.780 inches **Fastener Length:** Between 2.140 inches and 2.170 inches **Head Style:** Spline extended washer **Head Height:** Between 0.440 inches and 0.460 inches **Extended Washer Diameter:** Between 0.818 inches and 0.828 inches **Extended Washer Thickness:** Between 0.092 inches and 0.112 inches **Grip Diameter:** Between 0.4990 inches and 0.4995 inches **Head Minor Diameter:** 0.644 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 1.365 inches and 1.385 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material: Nickel alloy 718 **Material Specification:**

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5306-01-351-7070

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0