

View Online at <https://aerobasegroup.com/nsn/5306-01-351-9186>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.425 inches

**Fastener Length:**

Between 1.910 inches and 1.940 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.156 inches and 0.171 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Shoulder Diameter:**

0.3115 inches first shoulder and 0.3120 inches first shoulder

**Shoulder Length:**

1.490 inches first shoulder and 1.510 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.722 inches first hole and 1.772 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Iron alloy 660

**Material Specification:**

Ams5732 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0