NSN 5306-01-352-2624

Shear Bolt - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5506-01-552-2624
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.446 inches
Fastener Length:
Between 1.493 inches and 1.523 inches
Head Style:
Spline extended washer
Head Height:
Between 0.240 inches and 0.260 inches
Extended Washer Diameter:
Between 0.460 inches and 0.470 inches
Extended Washer Thickness:
Between 0.026 inches and 0.046 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Shank Unthreaded Hole Diameter:
0.076 inches first hole and 0.081 inches first hole
Head Minor Diameter:
0.318 inches
0.318 inches Thread Diameter:
Thread Diameter:
Thread Diameter: 0.250 inches
Thread Diameter: 0.250 inches Grip Length:
Thread Diameter: 0.250 inches Grip Length: Between 1.052 inches and 1.072 inches
Thread Diameter: 0.250 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi):
Thread Diameter: 0.250 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 28
Thread Diameter: 0.250 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi):
Thread Diameter: 0.250 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch
Thread Diameter: 0.250 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center:
Thread Diameter: 0.250 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.321 inches first hole
Thread Diameter: 0.250 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.321 inches first hole Material:
Thread Diameter: 0.250 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.321 inches first hole Material: Nickel alloy 718
Thread Diameter: 0.250 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.321 inches first hole Material: Nickel alloy 718 Material Specification:
Thread Diameter: 0.250 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.321 inches first hole Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response
Thread Diameter: 0.250 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.321 inches first hole Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment:
Thread Diameter: 0.250 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.321 inches first hole Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate

Unjf

NSN 5306-01-352-2624

Shear Bolt - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0