NSN 5306-01-352-6396

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-352-6396

view Offilite at https://defobasegroup.com/hsr//0000-01-002-0000
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.446 inches
Fastener Length:
Between 1.243 inches and 1.273 inches
Head Style:
Spline extended washer
Head Height:
Between 0.240 inches and 0.260 inches
Extended Washer Diameter:
Between 0.428 inches and 0.438 inches
Extended Washer Thickness:
Between 0.035 inches and 0.055 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Head Minor Diameter:
0.318 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.802 inches and 0.822 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
180000 pounds per square inch
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5306-01-352-6396

Shear Bolt - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A003b0