## NSN 5306-01-352-6397

Shear Bolt - Page 1 of 2

3a

View Online at https://aerobasegroup.com/nsn/5306-01-352-6397



## **Thread Class: Thread Direction: Right-hand Thread Length:** 0.446 inches Fastener Length: Between 1.556 inches and 1.586 inches **Head Style:** Spline extended washer **Head Height:** Between 0.240 inches and 0.260 inches **Extended Washer Diameter:** Between 0.460 inches and 0.470 inches **Extended Washer Thickness:** Between 0.026 inches and 0.046 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.081 inches first hole Head Minor Diameter: 0.318 inches **Thread Diameter:** 0.250 inches Grip Length: Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 220000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.384 inches first hole Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment:** Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjf

28

## NSN 5306-01-352-6397

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

