## NSN 5306-01-354-3720

Shear Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-354-3720 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.429 inches and 0.479 inches **Fastener Length:** Between 3.189 inches and 3.219 inches **Head Style:** Dished hexagon **Head Height:** Between 0.188 inches and 0.203 inches Width Between Flats: Between 0.554 inches and 0.564 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Unthreaded Hole Diameter:** 0.106 inches first hole and 0.116 inches first hole **Thread Diameter:** 0.375 inches **Grip Length:** Between 2.465 inches and 2.485 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 3.073 inches first hole and 3.113 inches first hole **Surface Finish:** 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material: Iron alloy 660 **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A003b0