NSN 5306-01-354-7707

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-354-7707

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.446 inches
Fastener Length: Between 1,743 inches and 1,773 inches
Head Style:
Spline extended washer
Head Height: Between 0.240 inches and 0.260 inches
Extended Washer Diameter:
Between 0.460 inches and 0.470 inches
Extended Washer Thickness:
Between 0.026 inches and 0.046 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches Head Minor Diameter:
Between 0.318 inches and 0.324 inches Thread Diameter:
0.250 inches
Grip Length: Between 1,302 inches and 1,322 inches
Thready Qty Per Inch (tpi):
28 Min Tangila Strangth (noi):
Min. Tensile Strength (psi):
220000 pounds per square inch Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification all treatment responses
Thread Series Designator:
Unif Shalf Life:
Shelf Life:
N/a

NSN 5306-01-354-7707

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0