## NSN 5306-01-354-7708



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-354-7708 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.538 inches **Fastener Length:** Between 1.898 inches and 1.928 inches **Head Style:** Spline extended washer **Head Height:** Between 0.302 inches and 0.322 inches **Extended Washer Diameter:** Between 0.521 inches and 0.531 inches **Extended Washer Thickness:** Between 0.051 inches and 0.071 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Head Minor Diameter:** 0.383 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.365 inches and 1.385 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** 

Unjf

Shelf Life:

N/a

## NSN 5306-01-354-7708

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0