

View Online at <https://aerobasegroup.com/nsn/5306-01-355-4845>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.594 inches

Fastener Length:

Between 3.454 inches and 3.484 inches

Head Style:

Dished hexagon

Head Height:

Between 0.281 inches and 0.296 inches

Width Between Flats:

Between 0.865 inches and 0.877 inches

Grip Diameter:

Between 0.5610 inches and 0.5615 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Thread Diameter:

0.562 inches

Grip Length:

Between 2.865 inches and 2.885 inches

Thread Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.262 inches first hole

Surface Finish:

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6409 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0