NSN 5306-01-355-8319

Shear Bolt - Page 1 of 2

Thread Class:

За



View Online at https://aerobasegroup.com/nsn/5306-01-355-8319

| Thread Direction: |
|--|
| Right-hand |
| Thread Length: |
| 0.323 inches |
| Fastener Length: |
| Between 1.620 inches and 1.650 inches |
| Head Style: |
| Dished hexagon |
| Head Height: |
| Between 0.110 inches and 0.125 inches |
| Width Between Flats: |
| Between 0.367 inches and 0.376 inches |
| Hole Diameter: |
| Between 0.046 inches and 0.056 inches |
| Grip Diameter: |
| Between 0.1845 inches and 0.1850 inches |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 1.302 inches and 1.322 inches |
| Hole Quantity: |
| 3 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hole Configuration Style: |
| Hexagon corners |
| Material: |
| Steel comp 4340 |
| Material Specification: |
| Mil-s-5000 military specification single material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416. type 2, cl 2 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| |

NSN 5306-01-355-8319

Shear Bolt - Page 2 of 2



| Specification Data: |
|--|
| 80205-nas6203-21h professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.