## NSN 5306-01-356-3184

Shear Bolt - Page 1 of 2

**Thread Class:** 

За



View Online at https://aerobasegroup.com/nsn/5306-01-356-3184

| Thread Direction:  |
|--|
| Right-hand   |
| Thread Length:   |
| 0.589 inches   |
| Fastener Length:   |
| Between 1.074 inches and 1.104 inches  |
| Head Style:  |
| Spline extended washer   |
| Head Height:   |
| Between 0.302 inches and 0.322 inches  |
| Extended Washer Diameter:  |
| Between 0.575 inches and 0.585 inches  |
| Extended Washer Thickness:   |
| Between 0.035 inches and 0.055 inches  |
| Hole Diameter:   |
| Between 0.050 inches and 0.060 inches  |
| Grip Diameter:   |
| Between 0.311 inches and 0.312 inches  |
| Head Minor Diameter:   |
| Between 0.383 inches and 0.389 inches  |
| Thread Diameter:   |
| 0.312 inches   |
| Grip Length:   |
| Between 0.490 inches and 0.510 inches  |
| Hole Quantity:   |
| 4  |
| Hole Type:   |
| Drilled  |
| Thready Qty Per Inch (tpi):  |
| 24   |
| Min. Tensile Strength (psi):   |
| 220000 pounds per square inch  |
| Hole Configuration Style:  |
| Spline   |
| Surface Finish:  |
| 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches all shoulders      |
| Material:  |
| Nickel alloy 718   |
| Material Specification:  |
| Ams5662 assn standard single material response or ams5663 assn standard single material response |
|  |

## NSN 5306-01-356-3184

Shear Bolt - Page 2 of 2

Fiig: A003b0

