NSN 5306-01-357-6225

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-357-6225

Three d Clares
Thread Class:
3a Thread Birastians
Thread Direction:
Right-hand Three differentials
Thread Length:
1.041 inches
Fastener Length:
Between 2.088 inches and 2.118 inches
Head Style:
Dished hexagon
Head Height:
Between 0.375 inches and 0.390 inches
Width Between Flats:
Between 1.052 inches and 1.065 inches
Grip Diameter:
Between 0.7480 inches and 0.7490 inches
Thread Diameter:
0.750 inches
Grip Length:
Between 1.052 inches and 1.072 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
16000 pounds per square inch
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ms 5732 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
81349-nas6712 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5306-01-357-6225

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0