# NSN 5306-01-357-8646

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-357-8646

Thread	Class:

3a

**Thread Direction:** 

Right-hand

# Thread Length:

0.735 inches

## Fastener Length:

Between 2.095 inches and 2.125 inches

#### **Head Style:**

Dished hexagon

Head Height:

Between 0.250 inches and 0.265 inches

### Width Between Flats:

Between 0.741 inches and 0.752 inches

#### Grip Diameter:

Between 0.4985 inches and 0.4995 inches

Thread Diameter:

0.500 inches

Grip Length:

Between 1.365 inches and 1.385 inches

## Thready Qty Per Inch (tpi):

20

### Min. Tensile Strength (psi):

160000 pounds per square inch

### Surface Finish:

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

Material:

Iron alloy 660

### **Material Specification:**

Ams 5731 assn standard single material response and ams 5737 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

### Surface Treatment Specification:

Q-c-416, type 2, cl 2 federal specification 13th treatment response

### **Thread Series Designator:**

Unjf

## **Specification Data:**

80205-nas6708 professional/industrial association standard

# Shelf Life:

N/a

# Unit Of Measure:

--

# NSN 5306-01-357-8646

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

