## NSN 5306-01-358-6672

Shoulder Bolt - Page 1 of 2

3a

View Online at https://aerobasegroup.com/nsn/5306-01-358-6672

**Thread Class: Thread Direction: Right-hand Thread Length:** 0.935 inches Fastener Length: Between 3.060 inches and 3.090 inches **Head Style:** Spline extended washer **Head Height:** Between 0.495 inches and 0.515 inches **Extended Washer Diameter:** Between 1.037 inches and 1.047 inches **Extended Washer Thickness:** Between 0.071 inches and 0.091 inches **Shoulder Diameter:** 0.5761 inches first shoulder and 0.5771 inches first shoulder Shoulder Length: 2.115 inches first shoulder and 2.135 inches first shoulder Head Minor Diameter: Between 0.711 inches and 0.717 inches **Thread Diameter:** 0.562 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c Shoulder Shape: Round first shoulder Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837, type 2 cl 2 military specification all treatment responses

## **Thread Series Designator:**

Unjf

18

## NSN 5306-01-358-6672

Shoulder Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

## Mil-std (military Standard):

Mil-c-8837 spec.

