NSN 5306-01-359-4622



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-359-4622 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.750 inches and 0.810 inches **Fastener Length:** 4.250 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.300 inches Width Between Flats: 0.348 inches **Extended Washer Diameter:** 0.438 inches **Extended Washer Thickness:** 0.060 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 3.440 inches and 3.500 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 130000 pounds per square inch **Hardness Rating:** 248.0 brinell standard and 341.0 brinell standard Minimum Yield Strength: 85000 pounds per square inch **Surface Finish:** 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams5731-85 assn standard single material response

Unjf

Shelf Life:

Thread Series Designator:

N/a

NSN 5306-01-359-4622

Machine Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0