

View Online at <https://aerobasegroup.com/nsn/5306-01-359-6301>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.630 inches and 0.690 inches

**Fastener Length:**

2.000 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.134 inches and 0.150 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Hole Diameter:**

0.047 inches

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 1.310 inches and 1.370 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Hole Configuration Style:**

Hexagon flats

**Surface Finish:**

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

**Material:**

Steel comp 8740

**Material Specification:**

Ams 6322 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0