## NSN 5306-01-359-7995

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-359-7995

**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** 0.438 inches Fastener Length: Between 0.560 inches and 0.590 inches **Head Style:** Spline extended washer **Head Height:** Between 0.195 inches and 0.215 inches **Extended Washer Diameter:** Between 0.349 inches and 0.350 inches **Extended Washer Thickness:** Between 0.017 inches and 0.037 inches **Grip Diameter:** Between 0.1885 inches and 0.1995 inches Head Minor Diameter: Between 0.173 inches and 0.188 inches **Thread Diameter:** 0.190 inches Grip Length: Between 0.315 inches and 0.335 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837, type 2, cdl 2 military specification single treatment response

**Thread Series Designator:** 

Unjf

## NSN 5306-01-359-7995

Shear Bolt - Page 2 of 2



**Specification Data:** 

96906-ms21296 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

## Mil-std (military Standard):

Mil-c-8837 spec.