

View Online at <https://aerobasegroup.com/nsn/5306-01-359-7995>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.438 inches

Fastener Length:

Between 0.560 inches and 0.590 inches

Head Style:

Spline extended washer

Head Height:

Between 0.195 inches and 0.215 inches

Extended Washer Diameter:

Between 0.349 inches and 0.350 inches

Extended Washer Thickness:

Between 0.017 inches and 0.037 inches

Grip Diameter:

Between 0.1885 inches and 0.1995 inches

Head Minor Diameter:

Between 0.173 inches and 0.188 inches

Thread Diameter:

0.190 inches

Grip Length:

Between 0.315 inches and 0.335 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

260000 pounds per square inch

Hardness Rating:

51.0 rockwell c and 54.0 rockwell c

Surface Finish:

32.0 microinches bearing surface of head32.0 microinches grip

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837, type 2, cdl 2 military specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

96906-ms21296 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.