# NSN 5306-01-360-1132

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-360-1132



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 1.005 inches and 1.555 inches

#### Fastener Length:

Between 6.015 inches and 6.045 inches

#### Head Style:

Spline extended washer

#### **Head Height:**

Between 0.552 inches and 0.572 inches

#### **Extended Washer Diameter:**

Between 1.153 inches and 1.163 inches

#### **Extended Washer Thickness:**

Between 0.080 inches and 0.100 inches

#### **Grip Diameter:**

Between 0.6230 inches and 0.6240 inches

#### Head Minor Diameter:

Between 0.774 inches and 0.782 inches

## Thread Diameter:

0.625 inches

Grip Length:

Between 4.490 inches and 5.010 inches

#### Thready Qty Per Inch (tpi):

18

#### Min. Tensile Strength (psi):

220000 pounds per square inch

#### Surface Finish:

32.0 microinches bearing surface of head32.0 microinches grip

#### Material:

Nickel alloy 718

#### Material Specification:

Ams5662 assn standard single material response or ams5663 assn standard single material response

#### Thread Series Designator:

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5306-01-360-1132

Shear Bolt - Page 2 of 2

Fiig: A003b0

