NSN 5306-01-360-6982

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-360-6982

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.578 inches
Fastener Length:
Between 1.313 inches and 1.343 inches
Head Style:
Dished hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.554 inches and 0.564 inches
Locking Feature:
Patch threads
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 0.740 inches and 0.760 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Material:
Plastic locking featuretitanium alloy uns r56400 fastener
Material Specification:
Ams 4928 assn standard single material response fastener or ams 4967 assn standard single material response fastener
Surface Treatment:
Aluminum fastener
Surface Treatment Specification:
Nas 4006 assn standard single treatment response fastener
Thread Series Designator:
Unjf
Specification Data:
80205-nas6806 professional/industrial association standard
Shelf Life:

N/a

NSN 5306-01-360-6982

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0