

View Online at <https://aerobasegroup.com/nsn/5306-01-360-6982>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.578 inches

Fastener Length:

Between 1.313 inches and 1.343 inches

Head Style:

Dished hexagon

Head Height:

Between 0.188 inches and 0.203 inches

Width Between Flats:

Between 0.554 inches and 0.564 inches

Locking Feature:

Patch threads

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 0.740 inches and 0.760 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Surface Finish:

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

Material:

Plastic locking featuretitanium alloy uns r56400 fastener

Material Specification:

Ams 4928 assn standard single material response fastener or ams 4967 assn standard single material response fastener

Surface Treatment:

Aluminum fastener

Surface Treatment Specification:

Nas 4006 assn standard single treatment response fastener

Thread Series Designator:

Unjf

Specification Data:

80205-nas6806 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0