NSN 5306-01-360-7590

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-360-7590

View Online at https://aerobasegroup.com/nsn/5306-01-360-7590
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.345 inches and 0.395 inches
Fastener Length:
Between 2.542 inches and 2.572 inches
Head Style:
Dished hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.429 inches and 0.439 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 2.177 inches and 2.197 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Material:
Iron alloy 660
Iron alloy 660
Iron alloy 660 Material Specification:
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment:
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Cadmium and chromate
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification:
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator:
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6304 professional/industrial association standard
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6304 professional/industrial association standard Shelf Life:

--

NSN 5306-01-360-7590

Shear Bolt - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A003b0