

View Online at <https://aerobasegroup.com/nsn/5306-01-360-8642>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.056 inches

Fastener Length:

4.431 inches

Head Style:

Double hexagon w/hole

Head Height:

0.711 inches

Width Between Flats:

Between 0.803 inches and 0.814 inches

Extended Washer Diameter:

Between 1.220 inches and 1.230 inches

Extended Washer Thickness:

0.178 inches

Hole Diameter:

0.055 inches

Grip Diameter:

Between 0.7480 inches and 0.7490 inches

Single Shear Strength:

108000 pounds per square inch

Thread Diameter:

0.750 inches

Grip Length:

3.375 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Hole Configuration Style:

Hexagon longitudinal hole

Material:

Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 6150 or steel comp 4140

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 ty2 cl3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0