Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-361-1184

| | Fhread Class: |
|---|--|
| | 2a |
| | دم Thread Direction: |
| | |
| | Right-hand Fhread Length: |
| | 2.000 inches |
| | Fastener Length: |
| | Between 1.938 inches and 2.000 inches |
| | Head Style: |
| | Hexagon |
| | Head Height: |
| | Between 0.455 inches and 0.483 inches |
| | Nidth Between Flats: |
| | Between 1.100 inches and 1.125 inches |
| | First Diameter From Head: |
| | 0.750 inches |
| | Second Diameter From Head: |
| | 0.580 inches |
| | Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| |).375 inches |
| ľ | Distance From Largest Bearing Surface Of Head To End Of Second Diameter: |
| | 0.431 inches |
| - | Thread Diameter: |
| (| 0.750 inches |
| - | Fhready Qty Per Inch (tpi): |
| | 10 |
| ļ | Min. Tensile Strength (psi): |
| | 120000 pounds per square inch |
| ļ | Externally Relieved Body Diameter Quantity: |
| | 1 |
| ļ | Material: |
| | Steel |
| ļ | Material Specification: |
| Ş | Sae j429 gr 5 assn standard single material response |
| ; | Surface Treatment: |
| (| Cadmium and chromate |
| ç | Surface Treatment Specification: |
| (| Qq-p-416 type 2 cl 2 federal specification all treatment responses |
| - | Thread Series Designator: |
| ι | Jnc |
| ; | Shelf Life: |
| г | N/a |

NSN 5306-01-361-1184

Externally Relieved Body Bolt - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0