

View Online at <https://aerobasegroup.com/nsn/5306-01-361-4920>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.551 inches

**Fastener Length:**

Between 4.911 inches and 4.941 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

0.348 inches

**Width Between Flats:**

0.419 inches

**Extended Washer Diameter:**

Between 0.521 inches and 0.531 inches

**Extended Washer Thickness:**

0.082 inches

**Grip Diameter:**

Between 0.3115 inches and 0.3120 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.081 inches first hole

**End Application:**

F-15

**Thread Diameter:**

0.3125 inches

**Grip Length:**

Between 4.365 inches and 4.385 inches

**Features Provided:**

Cetyl alcohol lubricant

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5002 spec.