

View Online at <https://aerobasegroup.com/nsn/5306-01-361-4920>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.551 inches

Fastener Length:

Between 4.911 inches and 4.941 inches

Head Style:

Double hexagon extended washer

Head Height:

0.348 inches

Width Between Flats:

0.419 inches

Extended Washer Diameter:

Between 0.521 inches and 0.531 inches

Extended Washer Thickness:

0.082 inches

Grip Diameter:

Between 0.3115 inches and 0.3120 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.081 inches first hole

End Application:

F-15

Thread Diameter:

0.3125 inches

Grip Length:

Between 4.365 inches and 4.385 inches

Features Provided:

Cetyl alcohol lubricant

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.