NSN 5306-01-361-7053

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-361-7053

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.480 inches |
| Fastener Length: |
| Between 1.215 inches and 1.245 inches |
| Head Style: |
| Double hexagon w/hole |
| Head Height: |
| Between 0.338 inches and 0.358 inches |
| Width Between Flats: |
| Between 0.367 inches and 0.376 inches |
| Extended Washer Diameter: |
| Between 0.521 inches and 0.531 inches |
| Extended Washer Thickness: |
| 0.082 inches |
| Hole Diameter: |
| Between 0.050 inches and 0.060 inches |
| Grip Diameter: |
| Between 0.3115 inches and 0.3120 inches |
| Thread Diameter: |
| 0.312 inches |
| Grip Length: |
| Between 0.740 inches and 0.760 inches |
| Hole Quantity: |
| 4 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 132000 pounds per square inch |
| Hole Configuration Style: |
| Double hexagon longitudinal hole |
| Product Name: |
| Navy special project |
| Material: |
| Nickel alloy 718 |
| Material Specification: |

Ams 5662 assn standard single material response

NSN 5306-01-361-7053

Close Tolerance Bolt - Page 2 of 2



| Surface Treatment: |
|---|
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A003b0