

View Online at <https://aerobasegroup.com/nsn/5306-01-361-9090>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.553 inches and 0.603 inches

**Fastener Length:**

Between 1.813 inches and 1.843 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.188 inches and 0.203 inches

**Width Between Flats:**

Between 0.554 inches and 0.564 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.240 inches and 1.260 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Surface Finish:**

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

**Special Features:**

After chrome plating, item is passivated per qqp35

**Material:**

Iron alloy 660

**Material Specification:**

Ams5731 assn standard single material response or ams5737 assn standard single material response

**Surface Treatment:**

Chromium

**Surface Treatment Specification:**

Qqc320, cl2a federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6706 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0