NSN 5306-01-361-9090

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-361-9090

View Crimine at https://acressassgreepreenwherweese CT CCT Costs
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.553 inches and 0.603 inches
Fastener Length:
Between 1.813 inches and 1.843 inches
Head Style:
Dished hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.554 inches and 0.564 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 1.240 inches and 1.260 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Special Features:
After chrome plating, item is passivated per qqp35
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5737 assn standard single material response
Surface Treatment:
Chromium
Surface Treatment Specification:
Qqc320, cl2a federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6706 professional/industrial association standard
Shelf Life:
N/a

NSN 5306-01-361-9090

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0