
# NSN 5306-01-361-9090

Shear Bolt - Page 1 of 2



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.553 inches and 0.603 inches

#### Fastener Length:

Between 1.813 inches and 1.843 inches

#### **Head Style:**

Dished hexagon

#### **Head Height:**

Between 0.188 inches and 0.203 inches

#### Width Between Flats:

Between 0.554 inches and 0.564 inches

#### Grip Diameter:

Between 0.3735 inches and 0.3745 inches

#### Thread Diameter:

0.375 inches

### Grip Length:

Between 1.240 inches and 1.260 inches

### Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

160000 pounds per square inch

#### Surface Finish:

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

#### **Special Features:**

After chrome plating, item is passivated per qqp35

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams5731 assn standard single material response or ams5737 assn standard single material response

#### Surface Treatment:

Chromium

#### Surface Treatment Specification:

Qqc320, cl2a federal specification single treatment response

### **Thread Series Designator:**

Unjf

## **Specification Data:**

80205-nas6706 professional/industrial association standard

## Shelf Life:

N/a



# NSN 5306-01-361-9090

Shear Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

