

View Online at <https://aerobasegroup.com/nsn/5306-01-362-4447>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.946 inches

**Fastener Length:**

Between 4.306 inches and 4.336 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.552 inches and 0.572 inches

**Extended Washer Diameter:**

Between 1.153 inches and 1.163 inches

**Extended Washer Thickness:**

Between 0.080 inches and 0.100 inches

**Grip Diameter:**

Between 0.6235 inches and 0.6240 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.146 inches first hole

**Head Minor Diameter:**

Between 0.774 inches and 0.782 inches

**Thread Diameter:**

0.625 inches

**Grip Length:**

Between 3.365 inches and 3.385 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.072 inches first hole

**Surface Finish:**

32.0 microinches bearing surface of head 32.0 microinches grip 32.0 microinches threads

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0