

View Online at <https://aerobasegroup.com/nsn/5306-01-362-4449>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.780 inches

Fastener Length:

Between 3.577 inches and 3.607 inches

Head Style:

Spline extended washer

Head Height:

Between 0.440 inches and 0.460 inches

Extended Washer Diameter:

Between 0.922 inches and 0.932 inches

Extended Washer Thickness:

Between 0.062 inches and 0.082 inches

Grip Diameter:

Between 0.4990 inches and 0.4995 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.111 inches first hole

Head Minor Diameter:

Between 0.644 inches and 0.651 inches

Thread Diameter:

0.500 inches

Grip Length:

Between 2.802 inches and 2.822 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.351 inches first hole

Surface Finish:

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0