## NSN 5306-01-362-5037

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-362-5037 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.578 inches **Fastener Length:** Between 2.063 inches and 2.093 inches **Head Style:** Dished hexagon **Head Height:** Between 0.188 inches and 0.203 inches Width Between Flats: Between 0.554 inches and 0.564 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Thread Diameter:** 0.3750 inches **Grip Length:** Between 1.490 inches and 1.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, ty ii, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6706 professional/industrial association standard Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5306-01-362-5037

Shear Bolt - Page 2 of 2



Demi			

No

Fiig:

A003b0