

View Online at <https://aerobasegroup.com/nsn/5306-01-363-1574>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.925 inches

**Fastener Length:**

Between 4.658 inches and 4.662 inches

**Head Style:**

Dee chamfer

**Head Diameter:**

2.000 inches

**Head Height:**

0.250 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.151 inches first hole

**First Diameter From Head:**

Between 0.997 inches and 0.998 inches

**Second Diameter From Head:**

Between 0.759 inches and 0.769 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 3.588 inches and 3.592 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 3.733 inches and 3.737 inches

**Thread Diameter:**

0.875 inches

**Thready Qty Per Inch (tpi):**

14

**Min. Tensile Strength (psi):**

280000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.398 inches first hole and 4.402 inches first hole

**Color:**

Gray

**Material:**

Steel

**Material Specification:**

Dms1935 mfr ref single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Dps9.28-1 mfr ref 1st treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0