NSN 5306-01-364-3565

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-364-3565 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.005 inches **Fastener Length:** Between 3.880 inches and 3.910 inches **Head Style:** Spline extended washer **Head Height:** Between 0.552 inches and 0.572 inches **Extended Washer Diameter:** Between 1.153 inches and 1.163 inches **Extended Washer Thickness:** Between 0.080 inches and 0.100 inches **Grip Diameter:** Between 0.6230 inches and 0.6240 inches **Head Minor Diameter:** Between 0.673 inches and 0.688 inches **Thread Diameter:** 0.625 inches **Grip Length:** Between 2.865 inches and 2.885 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 48.0 rockwell c and 50.0 rockwell c Material: Steel comp h11 **Material Specification:** Ams6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837 ty2 cl2 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5306-01-364-3565

Shear Bolt - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.